



SRL

Serial Number: _____

- Pass
- Remove From Service

Inspector Name: _____ Inspection Date: _____

Model Number: _____ Manufacture Date: _____ Date of First Use: _____

For more information, please see user instructions sent with the product at the time of shipment.

Operation

The lifeline must fully extract and retract smoothly without any slack being created upon controlled retraction.

- Not Retracting Not Extracting
- Does Not Extract / Retract Smoothly - Slack in Lanyard
- Pass
- Remove From Service

Comments: _____

Locking Mechanism

Check the operation of the unit by pulling smoothly on the lifeline, then pull sharply on the lifeline to engage the locking mechanism. Unit must not slip when locked.

- Not Locking Slips when Locked
- Pass
- Remove From Service

Comments: _____

Webbing

To inspect webbing, bend a portion of the webbing 6-8 inches into an upsidedown 'U' shape. Continue along all webbing inspecting for tears, cuts, fraying, abrasion, discoloration, burns, holes, mold, pulled or broken stitches, or other signs of wear and damage. Adjust all keepers, buckles, padding and D-ring to inspect webbing hidden by these components.

- Tears Cuts Fraying Abrasion
- Discoloration Burns Holes Mold
- Pass
- Remove From Service

Comments: _____

Stitching

Sewn terminations must be secure, complete, and not visibly damaged.

- Broken Missing Load Indicator Warning
- Pass
- Remove From Service

Comments: _____

Inspection Sheet



SRL

Housing / Casing

Housing or casing must be free from cracks, distortion or any other damage.

- Cracks
- Distortion

- Pass
- Remove From Service

Comments: _____

Cable

Cable must be inspected for kinks, broken strands, corrosion, abrasion, or other signs of wear and damage. Swaged terminations should be secure with the thimble tight, and not visibly damaged.

- Kinks
- Corrosion
- Abrasion
- Separation of Wire
- Chemical Attack
- Broken Wire
- Alteration
- Excessive Heating

- Pass
- Remove From Service

Comments: _____

Rope

Rope must be inspected for tears, cuts, fraying, abrasion, discoloration, burns, holes, mold, or other signs of wear and damage.

- Tears
- Cuts
- Fraying
- Abrasion
- Mold
- Discoloration
- Burns
- Holes
- Unsplicing
- Knots

- Pass
- Remove From Service

Comments: _____

Snap hooks / Carabiners

Snap hooks and carabiners on product must be able to self-close and lock. All hardware must be free of cracks, sharp edges, deformation, corrosion, or any evidence of defect.

- Does Not Close
- Cracks
- Deformation
- Corrosion
- Does Not Lock
- Sharp Edges
- Alteration
- Load Indicator Warning

- Pass
- Remove From Service

Comments: _____

Hardware

All hardware must be free of cracks, sharp edges, deformation, corrosion, or any evidence of defect.

- Cracks
- Sharp Edges
- Deformation
- Corrosion
- Chemical Attack
- Wear
- Alteration
- Excessive Heating

- Pass
- Remove From Service

Comments: _____

Labels

All markings must be legible and attached to the product.

- Illegible
- Missing

- Pass
- Remove From Service

Comments: _____

Inspection Sheet