



Lanyard

Serial Number: _____

- Pass
- Remove From Service

Inspector Name: _____ Inspection Date: _____

Model Number: _____ Manufacture Date: _____ Date of First Use: _____

For more information, please see user instructions sent with the product at the time of shipment.

Webbing

To inspect webbing, bend a portion of the webbing 6-8 inches into an upsidedown 'U' shape. Continue along all webbing inspecting for tears, cuts, fraying, abrasion, discoloration, burns, holes, mold, pulled or broken stitches, or other signs of wear and damage. Adjust all keepers, buckles, padding and D-ring to inspect webbing hidden by these components.

- | | | | | |
|-------------------------------------|-----------------------------|-------------------------------|--------------------------------|--|
| <input type="radio"/> Tears | <input type="radio"/> Cuts | <input type="radio"/> Fraying | <input type="radio"/> Abrasion | <input type="checkbox"/> Pass |
| <input type="radio"/> Discoloration | <input type="radio"/> Burns | <input type="radio"/> Holes | <input type="radio"/> Mold | <input type="checkbox"/> Remove From Service |

Comments: _____

Stitching

Sewn terminations must be secure, complete, and not visibly damaged.

- | | | | |
|------------------------------|-------------------------------|--|--|
| <input type="radio"/> Broken | <input type="radio"/> Missing | <input type="radio"/> Load Indicator Warning | <input type="checkbox"/> Pass |
| | | | <input type="checkbox"/> Remove From Service |

Comments: _____

Cable

Cable must be inspected for kinks, broken strands, corrosion, abrasion, or other signs of wear and damage. Swaged terminations should be secure with the thimble tight, and not visibly damaged.

- | | | | | |
|---------------------------------------|-----------------------------------|----------------------------------|--|--|
| <input type="radio"/> Kinks | <input type="radio"/> Corrosion | <input type="radio"/> Abrasion | <input type="radio"/> Separation of Wire | <input type="checkbox"/> Pass |
| <input type="radio"/> Chemical Attack | <input type="radio"/> Broken Wire | <input type="radio"/> Alteration | <input type="radio"/> Excessive Heating | <input type="checkbox"/> Remove From Service |

Comments: _____

Rope

Rope must be inspected for tears, cuts, fraying, abrasion, discoloration, burns, holes, mold, or other signs of wear and damage.

- | | | | | | |
|-------------------------------------|-----------------------------|-------------------------------|----------------------------------|-----------------------------|--|
| <input type="radio"/> Tears | <input type="radio"/> Cuts | <input type="radio"/> Fraying | <input type="radio"/> Abrasion | <input type="radio"/> Mold | <input type="checkbox"/> Pass |
| <input type="radio"/> Discoloration | <input type="radio"/> Burns | <input type="radio"/> Holes | <input type="radio"/> Unsplicing | <input type="radio"/> Knots | <input type="checkbox"/> Remove From Service |

Comments: _____

Inspection Sheet



Lanyard

Chain

Chain must be free from wear, nicks, cracks, breaks, gouges, stretch, bend, and discoloration from excessive temperatures.

- Wear
- Cracks
- Gouges
- Bent
- Pass
- Nicks
- Breaks
- Stretched
- Excessive Heating
- Remove From Service

Comments: _____

Snap hooks / Carabiners

Snap hooks and carabiners on product must be able to self-close and lock. All hardware must be free of cracks, sharp edges, deformation, corrosion, or any evidence of defect.

- Does Not Close
- Cracks
- Deformation
- Corrosion
- Pass
- Does Not Lock
- Sharp Edges
- Alteration
- Load Indicator Warning
- Remove From Service

Comments: _____

Hardware

All hardware must be free of cracks, sharp edges, deformation, corrosion, or any evidence of defect.

- Cracks
- Sharp Edges
- Deformation
- Corrosion
- Pass
- Chemical Attack
- Wear
- Alteration
- Excessive Heating
- Remove From Service

Comments: _____

Labels

All markings must be legible and attached to the product.

- Illegible
- Missing
- Pass
- Remove From Service

Comments: _____

Inspection Sheet